

FEATURES

| PRODUCT SPECIFICATIONS | |
|-------------------------|---|
| Footprint | 3267 x 6356 mm (including run-ups, extended) |
| Length | 5086 mm |
| Width | 3267 mm |
| Height | 2110 mm |
| Width Between Posts | 2700 mm |
| Width Between Platforms | 943 mm |
| Platform Length | 4580 mm |
| Platform Width | 520 mm |
| Run-Up Length | 945 mm extendable to 1270 mm |
| Motor | 3 Phase, 3 HorsePower, 415 Volt * (requires 3 Phase and Earth, 5 Amp) |
| Lifting Capacity | 4 tonnes |
| Maximum Raised Height | 1675 mm |
| Minimum Lowered Height | 170 mm |
| Minimum Lifting Time | 24 seconds |
| Concrete Depth | min 100 mm, mesh reinforced, min strength 25 MPa |
| Hydraulic Oil | high quality,46 weight, anti-wear |
| Gross Weight | 1440 kg |
| Shipping Dimensions | 5.0 x 1.15 x 0.6 metres |
| Finish | powder coated for added durability |
| Warranty | 3 years |

As the policy of Molnar Hoists is one of continuous improvement, the manufacturer reserves the right to change specifications without notice.

| Extra Wide | ideal for servicing trade vehicles, vans, four-wheel-drives or small trucks 'wheels free' |
|------------------------|--|
| Operational | 40mm incremental height adjustment |
| | push button to lift; lever to lower |
| | 4 beam pads included – J3BP |
| Safety | ${\bf deadmancontrols(automaticstopwhenreleased)}$ |
| | protection for cable breakage, overload and hydraulic failure |
| Service & Installation | comprehensive service manuals and installation instructions included |
| CUSTOMISATION | |
| | control unit position |
| Colour | extensive range of powder coated colours available |
| 4488RA-240VOLT * | optional single phase, 240 Volt motor (requires 240 Volts under load at motor, hard wired on 20 Amp circuit) |
| Extra Long | 1metre longer (6086 mm platforms) |
| OPTIONAL ACCESSORIES | |
| EXT-PAD | Beam Riser, Standard (for additional pick-up points) |
| EXT-PAD-LOW | Beam Riser, Lowered (for low profile vehicles) |
| AXLE-PU | Beam Riser, Axle (attach to rails for stable axle pick-up) |
| PL92-RB | Rubber Block, Standard (for cushioned lifting) |
| PL92-RB-40 | Rubber Block, Low Profile (for low profile vehicles) |
| SL02-NEST | Rubber Block Nest |
| 7252-023-01-A | Jack Stand, Wide (insert between platforms; turn upside down for a tool tray) |
| | |



For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097 E sales@molnarhoists.com.au www.molnarhoists.com.au

onwards & upwards