

HYDRAULIC DOUBLE-SCISSOR LIFT

JUMBO LIFT NT

FLEXIBILITY & TECHNOLOGY



WITH PATENTED
HyperFlow®
technology

WITH
TECHNOLOGY



THE MULTI-TASK EXPERT

- ✓ Very low construction height for above or in-ground installation
- ✓ Adjustable length of the lifting platforms
- ✓ NT and patented HyperFlow® Technologies:
100% hydraulic, 100% safe

3200 KG



CHOOSE YOUR JUMBO SIZE

JUMBO LIFT NT	3200
Lifting capacity (kg)	3200
Lifting time approx. (sec)	35
Lifting height (mm)	2000
Drive-on height (mm)	105
Installation depth (mm)	105
Recommended total width (mm)	2020
Platform width (mm)	610
Platform length (mm)	1460–2060
Motor (kW)	3
Power supply (V/Hz)	400/50

ACCESSORIES	3200
Rubber truncated pyramid pad	✓
Polymer pad 50 x 150 x 340 mm	✓
Polymer pad 100 x 150 x 340 mm	✓
Tuning ramps for low clearance vehicles / set = 4 units	✓
CE-Stop	✓

OPTIONAL SURFACE TREATMENT	3200
Oxygen care coated for corrosive environment	✓
Fire galvanized	✓

ACCESSORIES



Truncated pyramid pad



Polymer pads
50 x 150 x 340 mm



Polymer pads
100 x 150 x 340 mm

**More accessories
available**

Techn. changes and errors excepted. | Valid from 05 2017 © Otto Nussbaum GmbH & Co. KG | Korker Strasse 24 | 77694 Kehl-Bodersweier | Germany
Tel.: +49 (0) 7853 899 – 0 | Fax: +49 (0) 7853 8787 | info@nussbaum-group.de | nussbaum-group.de