

Designed to supplement the Molnar Hoist range, these lifting aids will improve workshop efficiency and safety

# LIFTING AID ACCESSORIES

**M  
O  
L  
N  
A  
R**



**HOISTS**

## EP10



### 'EXTENSION PAD'

Provides valuable extra clearance for four-wheel-drives and vans

Length	160 mm
Width	160 mm
Height - min	180 mm
Height - max	225 mm

For use on:

- Two Post Hoist Base
- Two Post Hoist All Rounder
- Two Post Hoist Asymmetric
- Two Post Hoist Four Tonne

## JB11 & JB11A



### 'AIR JACKING BEAM'

Raise a vehicle for wheel free service options

	JB11	JB11A
Width	1100 mm	1200 mm
Max span	1275 mm	<
Min height	75 mm (above platform)	
Max height	310 mm (above platform)	

For use on:

- Four Post Hoists

#### JB11A

Wide version for 'A' series

*Refer Air Jacking Beam Accessories brochure for related accessories*

## PL92-RB & PL92-RB-40



### 'RUBBER BLOCKS'

Solid rubber block for cushioned lifting

	PL92-RB	PL92-RB-40
Length	150 mm	150 mm
Width	100 mm	110 mm
Height	70 mm	40 mm

For use on:

- Platform Lift
- Scissor Lift
- Quick Lift
- Rubber Block Nest

## SLO2-NEST



### 'RUBBER BLOCK NEST'

Nest to house rubber blocks

Length	160 mm
Width	100 mm
Height	120 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Scissor Lift with beam
- Quick Lift with beam

## JJ3 & J3



### 'PICK-UP PADS'

Support and stabilises vehicle

	JJ3	J3
Diameter	140 mm	100 mm
Height - min	30 mm	30 mm
Height - max	80 mm	80 mm

For use on:

- Two Post Hoist Base
- Two Post Hoist All Rounder
- Two Post Hoist Asymmetric
- Two Post Hoist Four Tonne

## J3BP



### 'BEAM PAD'

Stabilises vehicles on beams  
Made from solid, long-lasting vulcanised rubber

Diameter	90 mm
Pad Height	30 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Scissor Lift with beam
- Quick Lift with beam



### EXT-PAD



Provides valuable extra clearance for four-wheel-drives and vans

Length	120 mm
Width	100 mm
Height - min	170 mm
Height - max	215 mm

### 'BEAM RISER, STANDARD'

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor Lift with beam

### EXT-PAD-LOW



For vehicles with low clearance

Length	120 mm
Width	100 mm
Height - min	140 mm
Height - max	175 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor Lift with beam

### 'BEAM RISER, LOWERED'

### AXLE-PU



For stable pick-up on axle; cradle head prevents lateral movement

Length	120 mm
Width	100 mm
Height - min	150 mm
Height - max	205 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor lift with beam

### 'BEAM RISER, AXLE'

### PL92-10



Provides valuable extra clearance for four-wheel-drives and vans

Length	120 mm
Width	100 mm
Height - min	155 mm
Height - max	195 mm

For use on:

- Platform Lift

### 'PLATFORM RISER'

### SLO2-SB



Provides more pick-up options

Length	1550 mm
Width	270 mm
Height	55 mm

For use on:

- Scissor Lift

### 'SCISSOR LIFT BEAM'

### QLSB-02



Provides more pick-up options

Length	1550 mm
Width	270 mm
Height	110 mm

For use on:

- Quick Lift

### 'QUICK LIFT BEAM'

### 7252-023-01 & 7252-023-01A



Insert between platforms; can be turned upside down and used as a tool tray

	7252-023-01	7252-023-01A
Length	1045 mm	1145 mm
Width	225 mm	<
Height	60 mm	<

For use on:

- Four Post Hoists
  - Four Post Rails Hoists
- 7252-023-01A**  
Wide version for 'A' series

### 'JACK STAND'

*As the policy of Molnar Hoists is one of continuous improvement, the manufacturer reserves the right to change specifications without notice.*

For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097  
E sales@molnarhoists.com.au  
www.molnarhoists.com.au

**onwards & upwards**

